

D301-LED

Prismatic Bollard









Stub up Projection 3' Max. Bolt Projection 1.5' + .25' Conduit Opening 3' Bolt Circle 4 5/8'

Description

Deco Lighting is proud to introduce its family of 7" diameter round bollard. These fixtures provide uniform illumination, superior spacing, and remarkable brightness control. Each bollard features rugged construction, and comes supplied with silicone gasketing to assure years of trouble free service.

Features

Job Information

- IES Type III Clear Prismatic Glass Refractor
- Extruded aluminum housings with flush mounting base.
- · Vandal resistant screws, Powdercoated finish.
- CRI: 83; Operating Temp: -40°C to +40°C
- Clear polycarbonate lenses, cast aluminum louvers
- · Mounting Kit with 8" Anchor Bolts included
- Standard color is bronze; also available in black and white.
- Contact factory for custom finishes.
- CSA listed for wet locations, IP65

Ordering Information

Example: (D301-LED-43-18-50-UNV-BZ-EM)

D301-LED						
Series	Height	Wattage/Lumen	Color Temp.	Voltage	Finish	Options
Prismatic Bollard	31 31" 43 43"	18 18W/1440 ³	40 4000K 50 5000K	UNV 122-277V	BZ Bronze ¹ BL Black WH White CU Custom ²	SP Surge Protection EM Emergency Operation

¹Standard color ²Contact factory for custom finishes



Deco Lighting practices a program of continuous product development, and as a result product specifications change frequently. We reserve the right to change product specifications without notice. Contact Deco for the latest product information.

Digitize your light?



D301-LEDPrismatic Bollard

Photometric Data



