

# **D443-LED**

## **Trapezoidal Performance Sconce**











#### Job Information

Type:	
Catalog #:	
Project:	
Comments:	
Prepared by:	







#### **Description**

The D443-LED trapezoidal sconce offers an excellent alternative to unsightly wall mounted fixtures. These architecturally refined luminaires are designed to integrate naturally to wall surfaces. Ideal for security, accent and perimeter lighting. Such as building facades, entry ways, garage doors, and tunnels.

#### **Features**

- Heavy duty two piece, die-cast aluminium powder coating construction.
- Heat and impact resistant tempered glass lens.
- One piece anodized aluminum designed reflector for best light efficiency.
- Fully gasketed lens assembly seals out external contaminants.
- Approx. Weight: 12lbs.
- Dark bronze powder coated finish for impact, corrosion and UV resistance.
- Integral cast-in aluminium hinges.
- Standard color is bronze; also available in black and white. Contact factory for custom finishes.
- cUL & UL 1598 listed for wet locations.
- Dark Sky compliant when ordered at 3000K.

### **Ordering Information**

Example: (D443-LED-30-40-UNV-BZ-PC)

D443-LED —								_⊢			
Series	Wattage/Lumen		Color Temp.		Voltage		Finish		Option		
Trapezoidal Performance Sconce	20 30 40 60	20W/2560 <sup>3.5</sup> 30W/3840 <sup>3.5</sup> 40W/5120 <sup>3.5</sup> 60W/7680 <sup>3.5</sup>	30 35 40 50	3000K 3500K 4000K 5000K <sup>4,5,6</sup>	UNV 347 480	120-277V 347V 480V (Step-Down Transformer used for 480V Divider)	BZ BL WH CU	Bronze <sup>1</sup> Black White Custom <sup>2</sup>	PC WSF WDF EMB	Photocell Wired Single Fuse Wired Double Fuse Intergal Emergency Backup	

<sup>1</sup> Standard for fixture





Deco Lighting practices a program of continuous product development, and as a result product specifications change frequently. We reserve the right to change product specifications without notice. Contact Deco for the latest product information.

<sup>&</sup>lt;sup>2</sup> Contact factory for custom finish <sup>3</sup> Initial Delivered Lumens <sup>4</sup> Standard Color Temp.