

## **D458-LED**

### **Slim Wall Sconce**








# 0 12 1/81

Job Information



### **Description**

The D458-LED Slim Wall Sconce is a wall mounted luminaire with fully shielded light source for up/down dual lighting for indoor or outdoor applications. This fixture is constructed from low copper aluminum cast, and is great for areas where space is an issue.

### **Features**

- Up/down dual lighting for indoor or outdoor applications
- Housing constructed from low copper aluminum cast
- Suitable for wet locations
- CSA listed
- Tempered glass diffuser
- · High corrosion resistant polyester powder coat finish
- Vandal resistant stainless steel screws
- Silicon gasket prevents contaminants from entering the fixture
- · Standard color is bronze; also available in black and white. Contact factory for custom finishes
- CRI: 80+
- 10 Year Limited Warranty

### **Ordering Information**

Example: (D458-LED-40-50-UNV-BZ-WSF)

D458-LED					
Series	Wattage/Lumen	Color Temp.	Voltage	Finish	Option
Slim Wall Sconce	20 20W (10 up/10 down)/1900 <sup>4</sup> 40 40W (20 up/20 down)/3880 <sup>4</sup> 60 60W (30 up/30 down)/5880 <sup>4</sup>	35 3500K 41 4100K 50 5000K <sup>5</sup>	UNV 120-277V 347 347V 480 480V (Step-Down Transformer used for 480V Divider)	BZ Bronze <sup>1</sup> BL Black WH White AL Aluminum SL Silver CU Custom <sup>2</sup>	180 Internal 180° Shield PC Photocell WSF Wired Single Fuse <sup>3</sup> WDF Wired Double Fuse <sup>3</sup> ELED Integrated Emergency LED secondary source battery pack (-4°F min. operating temp

Standard fixture color

<sup>2</sup> Contact factor for custom finishes <sup>3</sup> Please specify voltage (eg. 120V) <sup>4</sup> Delivered Lumens (5000K)

Standard color temp



Deco Lighting practices a program of continuous product development, and as a result product specifications change frequently. We reserve the right to change product specifications without notice. Contact Deco for the latest product information.

Digitize your light."