



DECO digital®

Powered By: NICHIA

DMB-LED

Surface Wall Mount Luminaire

Digitize your light.™

Job Information

Type:	
Catalog #:	
Project:	
Comments:	
Prepared by:	



Description

For applications that require a narrow-profile design with flat-bottom diffuser. Provides medium light levels in a compact fixture.


DMB-LED



Features

- Die formed, 22 gauge cold rolled steel housing assembly
- One piece end caps fasten with single acorn type nut
- Spot-welded for rigidity and clean appearance
- Knockouts are provided for flexible conduit attachment
- Diffuser is retained by a grooved formation running the length of the fixture and is held in place on both ends by the end caps
- Powder painted white
- High reflectivity coated, reflecting surfaces for improved efficiency
- Extruded white translucent linear prismatic acrylic diffuser provides soft illumination
- Approved to CSA and UL standards
- Ballasts and lamp holders are replaceable without removing the luminaire from the mounting surface

Dimensions



Ordering Information:

Example: (DMB-LED-2-45-30-UNV-DM)

Series	Length	Wattage/Lumen	Color Temp.	Voltage	Option
Surface Wall Mount Luminaire	2' 2"	22 22W/2175 <sup>1</sup>	30 3000K	UNV 120-277V	DM Dimming (0-10V)
	4'	35 35W/3450 <sup>1</sup>	35 3500K	120 120V	CSC Control Scope Connected
		45 45W/4450 <sup>1</sup>	40 4000K	277 277V	EM Emergency
		60 60W/5933 <sup>1</sup>	50 5000K		

<sup>1</sup> 2' Available in 22W, 4' Available in 35W, 45W & 60W



Digitize your light.™

LED Lighting

DECO®

LIGHTING