First Alert®

camera accessories

Description:

RG59 Coax Video & DC Power Cable - 100 Feet



Indoor/outdoor



Solid copper conductor for less voltage drop and better signal over longer distances - easier to handle

Combined video and DC power in one cable

BNC Male connections on video cable and 1 jack male, 1 plug female on DC power cable

Double shielded with aluminum foil insulation and braiding

Includes two adaptors to connect two lengths of cable together or to connect to an RCA jack

First Alert®

camera



- 1 100 ft BNC Cable
- 1 BNC female to BNC female adaptor
- 1 BNC Female to RCA male connector

Indoor/Outdoor Use a Low Noise & Interference & Interf

Product Specifications

General

Dimensions (Coiled on Card) Length Material Indoor/Outdoor Video Cable Terminations

DC Power Terminations

Adaptors (included)

10.25"W x 13.25"H x 2.25"D 100 feet See construction diagram below

(2) 75 ohm BNC Male: brass with tarnish resistant nickel plating, center contact gold plated brass (20 micro inches)

(1) Jack Male, (1) Plug Female: (2.10mm I.D./5.5mm O.D.), brass with tarnish resistant nickel plating (1) 75 Ohm BNC Female to RCA


Male Adaptor

(1) 75 Ohm BNC Female to BNC

Female Adaptor:

Cable Construction

Not all coax cables are created equally. First Alert's RG59 combined coax video and DC power cables use a solid copper conductor for less voltage drop and better signal over longer distances. This also makes the cable easier to handle versus other lower quality copper clad steel cables as it is less rigid and will not remain coiled. In addition, the cables are double shielded with aluminum foil insulation and braiding to help protect the video signal from interference. Each cable comes with BNC Male connections on each end of the video cable and 1 jack male, 1 plug female on the ends of the DC power cable (2.1mm I.D./5.5mm O.D.). We also supply two adaptor plugs for your convenience. One is a BNC female to BNC female adaptor to provide a way to connect two lengths of cable together. The other is a BNC Female to RCA male connector to attach cable to a TV RCA female (Yellow Video in) input. In addition, we offer cable that is fire rated FT-4/CMR UL approved for in-wall installations. All of these features ensure your customers of the highest quality installation.



Shipping Specifications

Individual Card

Dimensions 10.25"W x 13.25"H x 2.25"D
Weight 4.2 lbs.
Cube 0.18 ft3
UPC 0 29054 00881 7

Inner Carton

 Dimensions
 10.50"L x 10.37"W x 5.13"H

 Inner Pack
 2 Individual Cards

 Weight
 8.8 lbs.

 Cube
 0.32 ft3

 12of5
 500 29054 00881 2

Master Carton

Dimensions 21.53"L x 11.28"W x 11.32"H

Master Pack 8 (4 inner packs)

Weight 37.0 lbs.

Cube 1.59 ft3

120f5 100 29054 00881 4

Pallet Information

 Cases per layer
 6

 Number of Layers
 4

 Cases per Pallet
 24

 Units per Pallet
 192

 Cube
 42.4 ft3

 Weight
 953 lbs.



©2012 BRK Brands, Inc. a Jarden Corporation Company (NYSE:JAH) 3901 Liberty Street Road, Aurora, IL 60504-8122 Phone: 630-851-7330 Tech Services: 800-323-9005 First Alert is a registered trademark of the First Alert Trust BRK is a registered trademark of BRK Brands, Inc. CM3101