

First Alert[®]

SmartBridge[™]

REMOTE ACCESS**FULL D1 VIDEO SECURITY SYSTEM**

DESCRIPTION

8 CHANNEL / 8 CAMERA

H.264 1TB HDD DVR Full D1 System with 8 700TVL CMOS Cameras with Auto IR Cut Filter and Cold Temperature Performance, HDMI Output, Remote and USB Mouse



FULL D1 HIGH RESOLUTION
CLEAR, REAL-TIME VIDEO

All Channels have 3X Better Resolution than Standard CIF Systems



H.264
VIDEO
COMPRESSION

REC
Full D1
DIGITAL DVR
RECORDER

MOBILE PHONE/
WEB READY

1.0TB
DVR OPTIMIZED
SATA HDD

INDOOR/OUTDOOR
700 TVL CAMERAS

NIGHT
VISION

AUTO IR
CUT FILTER

COLD TEMP
PERFORMANCE

First Alert[®]**SmartBridge**[™]

REMOTE ACCESS

FULL D1 VIDEO SECURITY SYSTEM

CONTENTS:

- | | |
|--|-------------------------|
| 1 1TB H.264 Web-Ready Full D1 DVR System | 1 Splitter Cable |
| 8 Wired Indoor/Outdoor 700TVL Cameras | 1 6' Ethernet Cable |
| 1 Power Supply (Cameras and DVR) | 3 Window Warning Decals |
| 8 Camera Stands with Mounting Kits | 1 Quick Install Guide |
| 8 60ft. AV BNC/DC Power Cables | 1 Installation CD |
| 1 Remote Control | |
| 1 USB 2.0 Mouse | |



Back Panel

PRODUCT SPECIFICATIONS**General**

Operating Power	DC 12V
Power Consumption	15W without HDD/Average HDD during Read/Write 6W, 2A max on startup typical
Operating Temp	14 °F to 122 °F (-10 °C to 50°C)
Dimensions (DVR)	2.25"H x 12.63"W x 10.25"D
Dimensions (Camera & Stand)	3.25"H x 2.88"W x 6.25"D
Cable Length	60ft. per camera
Cable Type	AV BNC/DC Power
Remote Control	Included
Mouse	USB 2.0 Included
Backup	USB Port
Multi-view Mode	8 Channel: 1/4/8
Simultaneous Operations	Record, playback, mobile phone live view, backup, control, & remote access

Camera

Power Supply/Consumption	DC 12V/ 380mA (IR ON)
Operating Temp	-22°F to +122°F (-30°C to +50°C)
Image Sensor	1/4" CMOS (NTSC)
IR Cut Filter	Automatic
Lens	6mm
Horizontal Resolution	700 TV Lines
View Angle	34°
Number of Effective Pixels	NTSC - 720 x 480
Indoor/Outdoor	Both
Weather Resistant Rating	IP66
White Balance	Auto
Signal/Noise Ratio	> 48dB (AGC Off)
Gain Control	Auto
Backlight Compensation	Auto
Minimum Illuminance	0 Lux (IR on)
Gamma Characteristics	0.45
Shutter Speed	1/60 - 1/100,000 second
Infrared Wave length	850nm
Audio	No
Color	Yes

Night Vision

Number of infrared LED's	36
Distance	80 to 98 ft. (25m to 30m)

DVR

Compression Format	H.264 Video/G711 Audio
Video Format	NTSC & PAL

Video In	BNC 8-Channel, impedance 75Ω
Video Out	1 HDMI, 1 BNC & 1 VGA
Audio Input	2 RCA inputs, impedance 600Ω
Audio Output	1 RCA
VGA Output Supported	1024 x 768, 1280 x 1024
Recording Resolution	Full D1/CIF
Recording Frame Rate	NTSC: 1-30 fps
Recording Modes	Manual/Schedule/Motion/Alarm
DVR Storage Capacity	1TB included
HDD Interface/Memory Type	DVR Optimized SATA, up to 2TB
USB Port	Yes
LAN Port	Yes, 6' Ethernet Cable included
Alarm/Sensor Connection	4 Inputs/1 output
PTZ Camera Connection	RS485, Supports PELCO-P & D
Remote Access	Internet Explorer/MacOS X

SHIPPING SPECIFICATIONS**Individual Carton**

Dimensions	15.35"L x 12.6"W x 13.39"H
Weight	22.0 lbs.
Cube	1.50 ft ³
UPC	0 29054 01344 6

Master Carton

Dimensions	26.38"L x 16.14"W x 14.17"H
Master Pack	2
Weight	47.9 lbs.
Cube	3.49 ft ³
I2of5	200 29054 01344 0

Pallet Information

Cases per layer	3
Number of Layers	3
Cases per Pallet	9
Units per Pallet	18
Cube	35.2 ft ³
Weight	496 lbs.

BRK[®]

THE PROFESSIONAL STANDARD

brkelectronics.com

©2014 BRK Brands, Inc.
 a Jarden Corporation Company (NYSE:JAH)
 3901 Liberty Street Road, Aurora, IL 60504-8122
 Phone: 630-851-7330 Tech Services: 800-323-9005
 First Alert is a registered trademark of the First Alert Trust
 BRK is a registered trademark of BRK Brands, Inc.
 CM3188