

First Alert[®]

BRK SERIES

600TVL INDOOR COLOR CAMERA
WIRED CMOS CAMERA

DESCRIPTION:

1/4" CMOS Indoor Color Wired Mini Dome Camera
with Auto IR Cut Filter, Night Vision and 60' of Cable



INDOOR
600 TVL CAMERA



NIGHT
VISION



AUTO IR
CUT FILTER

BRK SERIES**S20CVL INDOOR COLOR CAMERA**
WIRED CMOS CAMERA**CONTENTS:**

- 1 Wired Indoor 600TVL Mini Dome Camera
- 1 Power Supply
- 1 Mounting Bracket and Hardware
- 1 60ft. AV BNC/DC Power Cable
- 1 Manual

**PRODUCT SPECIFICATIONS****General**

Operating Power	DC 12V
Power Consumption	225mA (IR ON)
Operating Temp	14 °F to 122 °F (-10 °C to 50°C)
Dimensions (Camera & Stand)	3.625 Dia x 2.69" H
Cable Length	60ft. included
Cable Type	AV BNC/DC Power

Camera

Image Sensor	1/4" CMOS (NTSC)
IR Cut Filter	Automatic
Lens	6mm
Horizontal Resolution	600 TV Lines
View Angle	62 degrees
Number of Effective Pixels	NTSC - 656 x 492
Indoor/Outdoor	Indoor only
Weather Resistant Rating	None
White Balance	Auto
Signal/Noise Ratio	> 48dB (AGC Off)
Gain Control	Auto
Backlight Compensation	Auto
Minimum Illuminance	0 Lux (IR on)
Gamma Characteristics	0.45
Shutter Speed	1/60 - 1/100,000 second
Infrared Wave length	850nm
Audio	No
Color	Yes

Night Vision

Number of infrared LED's	32
Distance	80 to 98 ft. (25m to 30m)

SHIPPING SPECIFICATIONS**Individual Carton**

Dimensions	6.75"L x 3.375"W x 6.75"H
Weight	1.8 lbs.
Cube	0.09 ft3
UPC	0 29054 01104 6

Inner Carton

Dimensions	14.13"L x 7.25"W x 7.25"H
Inner Pack	4
Weight	7.8 lbs.
Cube	0.43 ft3
I2of5	400 29054 01104 4

Master Carton

Dimensions	15.25"L x 14.75"W x 15.5"H
Master Pack	16 (4 inner packs)
Weight	33.0 lbs.
Cube	2.0 ft3
I2of5	600 29054 01104 8

Pallet Information

Cases per layer	6
Number of Layers	3
Cases per Pallet	18
Units per Pallet	288
Cube	39.4 ft3
Weight	659 lbs.