



BRK SERIES

H.264 DIGITAL DVR RECORDING WIRED CAMERA SYSTEM

DESCRIPTION:

8 Channel H.264 1TB HDD DVR Camera System with 4 520TVL CMOS Cameras, Remote and USB Mouse



Includes 4 Cameras

H.264
VIDEO
COMPRESSION

REC
DIGITAL DVR
RECORDER

MOBILE PHONE/
WEB READY

1.0TB
DVR OPTIMIZED
SATA HDD

INDOOR/OUTDOOR
520 TVL CAMERAS

NIGHT
VISION

BRK SERIES

**H.264 DIGITAL DVR
RECORDING WIRED CAMERA SYSTEM**

CONTENTS:

- | | |
|---------------------------------------|-------------------------|
| 1 1TB H.264 Web-Ready DVR System | 1 Splitter Cable |
| 4 Wired Indoor/Outdoor 520TVL Cameras | 1 6' Ethernet Cable |
| 1 Power Supply (Cameras and DVR) | 2 Window Warning Decals |
| 4 Camera Stands with Mounting Kits | 1 Quick Install Guide |
| 4 60ft. AV BNC/DC Power Cables | 1 Manual (pdf only) |
| 1 Remote Control | 1 Installation CD |
| 1 USB 2.0 Mouse | |



Front Panel



Back Panel

PRODUCT SPECIFICATIONS

General

Operating Power	DC 12V
Operating Temp	14 °F to 122 °F (-10 °C to 50°C)
Dimensions (DVR)	2.4"H x 11.8"W x 9.6"D
Dimensions (Camera & Stand)	5.5"H x 3.68"W x 3.63"D
Cable Length	60ft. per camera
Cable Type	AV BNC/DC Power
Remote Control	Included
Mouse	USB 2.0 Included
Backup	USB Port
Multi-view Mode	8 Channel: 1/4/8
Simultaneous Operations	Real hexaplex operation - record, playback, mobile phone live view, backup, control, & remote access

Camera

Operating Power	DC 12V
Operating Temp	14 °F to 122 °F (-10 °C to 50°C)
Image Sensor	1/3.6" CMOS (NTSC)
Lens	6.0 mm
Horizontal Resolution	520 TV Lines
View Angle	50 degrees
Number of Effective Pixels	NTSC - 656 x 492
Indoor/Outdoor	Both
Weather Resistant Rating	IP65
White Balance	Auto
Signal/Noise Ratio	> 48dB (AGC Off)
Gain Control	Auto
Backlight Compensation	Auto
Minimum Illuminance	0 Lux (IR on)
Gamma Characteristics	0.45
Shutter Speed	1/60 - 1/100,000 second
Infrared Wave length	850nm
Audio	No
Color	Yes

Night Vision

Number of infrared LED's	30
Distance	minimum 80 ft.

DVR

Compression Format	H.264 Video/ADPCM Audio
Video Format	NTSC & PAL
Video In	BNC 8-Channel, impedance 75Ω
Video Out	1 BNC & 1 VGA
Audio Input	8 RCA inputs, impedance 600Ω
Audio Output	1 RCA

VGA Output Supported

800 x 600, 1024 x 768, 1280 x 1024, 1366 x 768, 1440 x 900

- Recording Resolution D1/HD1/CIF
- Recording Frame Rate NTSC 480 chipset: up to 420 fps
- Recording Modes Manual/Schedule/Motion
- DVR Storage Capacity 1TB included
- HDD Interface/Memory Type DVR Optimized SATA, up to 2TB
- USB Port Yes
- LAN Port Yes, 6' Ethernet Cable included
- Alarm/Sensor Connection 8 Inputs/1 output
- PTZ Camera Connection RS485, Supports PELCO-P & D

SHIPPING SPECIFICATIONS

Individual Carton

Dimensions	14.25"L x 7.25"W x 15.75"H
Weight	14.7 lbs.
Cube	0.94 ft3
UPC	0 29054 00982 1

Master Carton

Dimensions	16.00"L x 15.00"W x 17.00"H
Master Pack	2
Weight	31.4 lbs.
Cube	2.36 ft3
I2of5	200 29054 00982 5

Pallet Information

Cases per layer	6
Number of Layers	3
Cases per Pallet	18
Units per Pallet	36
Cube	46.7 ft3
Weight	630 lbs.



©2012 BRK Brands, Inc.
a Jarden Corporation Company (NYSE:JAH)
3901 Liberty Street Road, Aurora, IL 60504-8122
Phone: 630-851-7330 Tech Services: 800-323-9005
First Alert is a registered trademark of the First Alert Trust
BRK is a registered trademark of BRK Brands, Inc.
CM3108