# First Alert®

### **BRK SERIES**

### H.264 DIGITAL DVR RECORDING WIRED CAMERA SYSTEM

#### **DESCRIPTION:**

8 Channel H.264 1TB HDD DVR Camera System with 8 600TVL CMOS Cameras with Auto IR Cut Filter and Cold Temperature Performance, Remote and USB Mouse



**H.264** 

VIDEO COMPRESSION



DIGITAL DVR RECORDER



MOBILE PHONE/ WEB READY



DVR OPTIMIZED SATA HDD



INDOOR/OUTDOOR 600 TVL CAMERAS



NIGHT VISION



AUTO IR CUT FILTER



COLD TEMP PERFORMANCE

### **BRK SERIES**

## H.264 DIGITAL DVR RECORDING WIRED CAMERA SYSTEM

#### **CONTENTS:**

- 1TB H.264 Web-Ready DVR System
- Wired Indoor/Outdoor 600TVL Cameras 8
- Power Supply (Cameras and DVR) 1
- Camera Stands with Mounting Kits
- 60ft. AV BNC/DC Power Cables
- Remote Control
- **USB 2.0 Mouse**

- Splitter Cable
- 6' Ethernet Cable 1
- 2 Window Warning Decals
- 1 Quick Install Guide
- Manual (pdf only)
- 1 Installation CD



Front Panel



**Back Panel** 

#### PRODUCT SPECIFICATIONS

#### General

**Operating Power** 

**Power Consumption** 

**Operating Temp** 

Dimensions (DVR) Dimensions (Camera & Stand)

Cable Length Cable Type

Remote Control

Mouse Backup

Multi-view Mode

Simultaneous Operations

**DC 12V** 

6W without HDD/Average HDD during Read/Write 6W, 2A max

on startup typical

14 °F to 122 °F (-10 °C to 50°C)

2.4"H x 11.8"W x 9.6"D 3.25"H x 2.88"W x 6.25"D

60ft. per camera AV BNC/DC Power

Included

USB 2.0 Included

**USB Port** 

8 Channel: 1/4/8

DC 12V/ 225mA (IR ON)

1/4" CMOS (NTSC)

NTSC - 656 x 492

> 48dB (AGC Off)

0 Lux (IR on)

Automatic

600 TV Lines

62 degrees

6mm

**Both** 

**IP66** 

Auto

Auto

Auto

0.45

Nο

Yes

850nm

Real hexaplex operation - record. playback, mobile phone live view, backup, control, & remote access

-22°F to +122°F ( -30°C to +50°C)

Camera

Power Supply/Consumption

**Operating Temp** Image Sensor IR Cut Filter

Lens

Horizontal Resolution

View Anale

**Number of Effective Pixels** 

Indoor/Outdoor

Weather Resistant Rating

White Balance

Signal/Noise Ratio

**Gain Control** 

**Backlight Compensation** Minimum Illuminance

**Gamma Characteristics Shutter Speed** 

Infrared Wave length

Audio Color

#### **Night Vision**

Number of infrared LED's

Distance

**DVR** 

**Compression Format** Video Format

36

80 to 98 ft. (25m to 30m)

1/60 - 1/100,000 second

H.264 Video/ADPCM Audio NTSC & PAL

Video In Video Out

Audio Input

**Audio Output** 

VGA Output Supported

Recording Resolution Recording Frame Rate **Recording Modes** 

**DVR Storage Capacity** 

**HDD Interface/Memory Type** 

**USB Port** LAN Port

Alarm/Sensor Connection PTZ Camera Connection

Remote Access

BNC 8-Channel, impedance 75Ω

1 BNC & 1 VGA

8 RCA inputs, impedance 600Ω

1 RCA

800 x 600, 1024 x 768, 1280 x 1024, 1366 x 768, 1440 x 900

D1/HD1/CIF

NTSC 480 chipset: up to 420 fps

Manual/Schedule/Motion

1TB included

DVR Optimized SATA, up to 2TB

Yes, 6' Ethernet Cable included

8 Inputs/1 output

RS485, Supports PELCO-P & D

Internet Explorer/MacOS X

#### SHIPPING SPECIFICATIONS

#### **Individual Carton**

**Dimensions** 14.25"L x 10.5"W x 16.00"H Weight 23.4 lbs.

1.39 ft3 Cube **UPC** 0 29054 01102 2

**Master Carton** 

**Dimensions** 21.75"L x 15.00"W x 17.50"H

Master Pack

Weight 49.2 lbs. Cube 3.31 ft3

I2of5 200 29054 01102 6

#### **Pallet Information**

5 Cases per layer Number of Layers 2 Cases per Pallet 10 Units per Pallet 20 Cube 38.2 ft3 Weight 557 lbs.



©2012 BRK Brands, Inc. a Jarden Corporation Company (NYSE:JAH) 3901 Liberty Street Road, Aurora, IL 60504-8122 Phone: 630-851-7330 Tech Services: 800-323-9005 First Alert is a registered trademark of the First Alert Trust BRK is a registered trademark of BRK Brands, Inc.