

BRK SERIES

H.264 DIGITAL DVR RECORDING WIRED CAMERA SYSTEM

DESCRIPTION:

8 Channel H.264 1TB HDD DVR Camera System with an 18.5" LCD Widescreen Monitor, eight 600TVL CMOS Cameras with Auto IR Cut Filter and Cold Temperature Performance, Remote and USB Mouse







R MOBILE PHONE/ R WEB READY **T.O**B DVR OPTIMIZED SATA HDD

INDOOR/OUTDOOR 600 TVL CAMERAS NIGHT

VISION

AUTO IR

CUT FILTER

COLD TEMP PERFORMANCE

BRK SERIES

H.264 DIGICAL DVR RECORDING WIRED CAMERA SYSTEM

CONTENTS:

- 1TB H.264 Web-Ready DVR System 1
- Wired Indoor/Outdoor 600TVL Cameras 8
- Power Supply (Cameras and DVR) 1
- 8 **Camera Stands with Mounting Kits**
- 8 60ft. AV BNC/DC Power Cables
- **Remote Control** 1
- **USB 2.0 Mouse**

- **Splitter Cable** 1 1
- 6' Ethernet Cable 2
- Window Warning Decals 1
- **Quick Install Guide** 1 Manual (pdf only)
- 1 Installation CD



Back Panel

PRODUCT SPECIFICATIONS

General

Operating Power Power Consumption

Operating Temp Dimensions (DVR) Dimensions (Camera & Stand) **Dimensions** (Monitor) Cable Length Cable Type **Remote Control** Mouse Backup Multi-view Mode Simultaneous Operations

Monitor

Power Supply/Consumption **Display Size Display Type Dvnamic Contrast Ratio Pixel Pitch** Resolution **Response Time**

Camera

Power Supply/Consumption **Operating Temp** Image Sensor IR Cut Filter Lens **Horizontal Resolution View Angle** Number of Effective Pixels Indoor/Outdoor Weather Resistant Rating White Balance Signal/Noise Ratio Gain Control **Backlight Compensation** Minimum Illuminance **Gamma Characteristics** Shutter Speed Infrared Wave length Audio Color Number of infrared LED's Distance

DC 12V

6W without HDD/Average HDD during Read/Write 6W, 2A max on startup typical 14 °F to 122 °F (-10 °C to 50°C) 2.4"H x 11.8"W x 9.6"D 3.25"H x 2.88"W x 6.25"D 13 3/4"H x 17 3/4"W x 5 3/4"D 60ft. per camera AV BNC/DC Power Included USB 2.0 Included USB Port 8 Channel: 1/4/8 Real hexaplex operation - record, playback, mobile phone live view, backup, control, & remote access

DC 12V 5A/11W 18.5" (16:9) LED SLIM Active matrix TFT 5.000.000:1 0.239 1366 x 768 @ 60Hz 2mS

DC 12V/ 225mA (IR ON) -22°F to +122°F (-30°C to +50°C) 1/4" CMOS (NTSC) Automatic 6mm 600 TV Lines 62 degrees NTSC - 656 x 492 Both **IP66** Auto > 48dB (AGC Off) Auto Auto 0 Lux (IR on) 0.45 1/60 - 1/100,000 second 850nm No Yes 36 80 to 98 ft. (25m to 30m)

DVR

Compression Format Video Format Video In Video Out Audio Input Audio Output VGA Output Supported

Recording Resolution Recording Frame Rate **Recording Modes DVR Storage Capacity** HDD Interface/Memory Type **USB** Port I AN Port Alarm/Sensor Connection PTZ Camera Connection **Remote Access**

H.264 Video/ADPCM Audio **NTSC & PAL** BNC 8-Channel, impedance 75Ω 1 BNC & 1 VGA 8 RCA inputs, impedance 600Ω 1 RCA 800 x 600, 1024 x 768, 1280 x 1024, 1366 x 768, 1440 x 900 D1/HD1/CIF NTSC 480 chipset: up to 420 fps Manual/Schedule/Motion **1TB** included DVR Optimized SATA, up to 2TB Yes Yes, 6' Ethernet Cable included 8 Inputs/1 output RS485, Supports PELCO-P & D Internet Explorer/MacOS X

SHIPPING SPECIFICATIONS

Individual Carton

Dimensions

Cube UPC Master Carton

Weight

Dimensions Master Pack

Weight Cube l2of5

Pallet Information

Cases per layer Number of Layers Cases per Pallet Units per Pallet Cube Weight

brkelectronics.com



©2012 BRK Brands, Inc. a Jarden Corporation Company (NYSE:JAH) 3901 Liberty Street Road, Aurora, IL 60504-8122 Phone: 630-851-7330 Tech Services: 800-323-9005 First Alert is a registered trademark of the First Alert Trust BRK is a registered trademark of BRK Brands, Inc. CM3153

20.25"L x 13.13"W x 15.63"H 29.21 lbs. 2.4 ft3 0 29054 01124 4

21.0"L x 14.0"W x 16.75"H 31.76 lbs. 2.85 ft3 200 29054 01124 8

6

3

18

18

62.9 ft3

637 lbs.