6 INCH DEEP BAFFLE LED DOWN LIGHT

J	Μ	W	Ά	Y	INC.®
	A CONSOLI	DATED LIG	HTING GF	ROUP	

Project:

Prepared by: Comments Date:



FEATURES

- 5 Year Warranty
- Direct Retrofit 65W Incandescent
- Energy Savings of up to 80%
- Cast Aluminum Housing & Trim
- Standard E26 Edison Screw Base Adapter
- Lumen Maintenance over 70% @ 50,000+ Hours
- Compatible w/Most Triac Phase-Control Dimmers
- No UV/IR Radiation, No Toxic Mercury

OPTICS

- Deep Baffle Lens Trim
- Frosted White Lens
- Regressed Reflector
- Compatible with most 6" Housings

TRIM ORDERING OPTIONS

APPLICATIONS

- Ceiling Installations for General Ambient Lighting in Homes, Offices & Public Facilities
- Retail Store Lighting
- Museums, Galleries, Showrooms
- Hotels, Hospitality Areas
- Hospitals, Clinics, Workrooms
- Corridors, Lobbies, Stairways

CERTIFICATIONS

- cETLus Listed
- Energy Star Listed for Rebate and Tax Incentive Programs
- California Title 24 Compliant
- Rated for Wet-Locations

<u>6" LED Deep Baffie Down Light</u>								
MODEL NUMBER	KELVIN (CCT)	WATTS	LUMENS	<u>CRI</u>	TRIM COLOR			
EVL6732DBWH27	2700K	11.00	674	91	WHITE BAFFLE			
EVL6732DBWH30	3000K	11.00	674	93	WHITE BAFFLE			
EVL6732DBWH40	4000K	10.94	698	92	WHITE BAFFLE			

DIMMING COMPATIBILITY Recommended 120v Incandescent Dimmers Dimming Range: 100% - 10% LED Trims Described Herein are Compatible with most Standard 120V Incandescent Forward Phase-Leading and 120V Electronic Low-Voltage Leviton IPL06-10Z Leviton 6674-POW Phase-Trailing Edge Dimmers. Dimming Range Varies with the Dimmer Control Used. SPECIFICATIONS 45C 50 Warranty 5 Years Max. Ambient Temp: R-Value: Beam Angel: 93 deg. 50,000 hrs -18C Power Factor: Expected Life Min. Ambient Temp: >0.90 THD: <20%

















JIMWAY, INC. Main (310) 886-3718 | Fax (310) 886-3719

Specifications subject to change without notice

© Copyright JIMWAY, INC., 2016

20101 South Santa Fe Avenue

Rancho Dominguez, CA 90221