



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

Warwick (WAR)

LSI Abolite® LED Warwick



OVERVIEW

Lumen Range	1,250 - 1,700
CCT	27/30/35/40/50K
Wattage Range	9.3 - 12.8

QUICK LINKS

[Ordering Guide](#)[Performance](#)[Photometrics](#)[Dimensions](#)

FEATURES & SPECIFICATIONS

Construction

- Heavy gauge spun aluminum with a thermally cured high quality polyester powder coat finish.
- Integrated power supply built into the fixture allowing the RLM to be connected directly to line voltage.
- Manufactured in the USA

Optical System

- Available in 5000K, 4000K, 3500K, 3000K, and 2700K color temperatures
- Minimum CRI of 80

Electrical

- Standard Universal Voltage (120-277 Vac) Input 50/60Hz
- 0-10V dimming, 5% standard
- Operating Temperature -30°C to +50°C (-22°F to +122°F)

Installation

- Fixture can be top or side mounted using a 3/4" gooseneck or stem.
- Pre-wired with 96" leads standard.
- Fixed hub tapped for 3/4" NPT conduit.
- Glass globe is required.
- Not designed for uplight applications.

Warranty

- LSI luminaires carry a 5-year limited warranty. Refer to <https://www.lsicorp.com/resources/terms-conditions-warranty/> for more information.

Listings

- UL Listed
- Suitable for wet locations



**ORDERING GUIDE**[Back to Quick Links](#)TYPICAL ORDER EXAMPLE: **WAR 616 17L UNV 35 CGG6 GRD LDS96WL**

Prefix	Lumen Package	Voltage	Color Temp	Lens	Finish	Mounting Options
WAR 610¹ WAR 616¹ WAR 610W² WAR 616W²	12L - 1250 lms 15L - 1500 lms 17L - 1700 lms INC³ - Incandescent	UNV - Universal Voltage (120/277V) 120 - INC	50 - 5,000K 40 - 4,000K 35 - 3,500K 30 - 3,000K 27 - 2,700K (blank) - INC	CGG6 - Clear Glass Globe 6-3/4" FGG6 - Frosted Glass Globe 6-3/4" PGG6 - Prismatic Glass Globe 6-3/4"	GWT - Gloss White GBK - Gloss Black GRD - Gloss Red BBL - Bright Blue DKG - Dark Green SLV - Silver MBK - Matte Black RST - Rust HCP - Hammered Copper	LDS96WL - Prewired leads. For use with stem or bracket mounting in wet or indoor locations.

1. Top Mount
2. Side Mount
3. Lamp supplied by other. E26 MED Base socket.

Accessory Ordering Information

CANOPY ORDERING INFORMATION (Accessories are field installed)	
Description	Order Number
3/4" (19mm) Tap Decorative Box Cover Aligner - Gloss White	BA 3 GWT

Standard finish is Gloss White Powder; other RLM colors available.

GOOSE NECK BRACKETS ORDERING INFORMATION (Accessories are field installed)	
Description	Order Number
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN A 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN B 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN C 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN E 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN F 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN G 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN H 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN K 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN P 3 GWT
3/4" (19mm) Aluminum Gooseneck Bracket - Gloss White	GN U 3 GWT

- Standard finish is Gloss White Powder; other RLM colors available.

STEM ORDERING INFORMATION (Accessories are field installed)	
Description	Order Number
3/4" x 3" (19mm x 76mm) Aluminum Stem - Gloss White	STM 3 3 GWT
3/4" x 6" (19mm x 152mm) Aluminum Stem - Gloss White	STM 6 3 GWT
3/4" x 12" (19mm x .4m) Aluminum Stem - Gloss White	STM 12 3 GWT
3/4" x 18" (19mm x .5m) Aluminum Stem - Gloss White	STM 18 3 GWT
3/4" x 24" (19mm x .6m) Aluminum Stem - Gloss White	STM 24 3 GWT
3/4" x 36" (19mm x .9m) Aluminum Stem - Gloss White	STM 36 3 GWT
3/4" x 48" (19mm x 1.2m) Aluminum Stem - Gloss White	STM 48 3 GWT
3/4" x 60" (19mm x 1.5m) Aluminum Stem - Gloss White	STM 60 3 GWT
3/4" x 72" (19mm x 1.8m) Aluminum Stem - Gloss White	STM 72 3 GWT

- Standard finish is Gloss White Powder; other RLM colors available.

SIDE MOUNT STEM BRACKET ORDERING INFORMATION (Accessories are field installed)	
Description	Order Number
3/4" x 8" (19mm x 203mm) Side Mount Stem Bracket - Gloss White	GN I8 3 GWT
3/4" x 10" (19mm x 254mm) Side Mount Stem Bracket - Gloss White	GN I10 3 GWT
3/4" x 12" (19mm x 305mm) Side Mount Stem Bracket - Gloss White	GN I12 3 GWT
3/4" x 14" (19mm x 356mm) Side Mount Stem Bracket - Gloss White	GN I14 3 GWT
3/4" x 18" (19mm x 457mm) Side Mount Stem Bracket - Gloss White	GN I18 3 GWT

Standard finish is Gloss White Powder; other RLM colors available.
Side mount stem to be used with "W" option.**PERFORMANCE**[Back to Quick Links](#)

DELIVERED LUMENS																	
Lumen Package	CRI	2700K			3000K			3500K			4000K			5000K			Wattage
		Delivered Lumens	Efficacy	BUG Rating	Delivered Lumens	Efficacy	BUG Rating	Delivered Lumens	Efficacy	BUG Rating	Delivered Lumens	Efficacy	BUG Rating	Delivered Lumens	Efficacy	BUG Rating	
12L	80	1067	115	B1-U3-G1	1188	128	B1-U3-G1	1058	114	B1-U3-G1	1056	114	B1-U3-G1	1056	114	B1-U3-G1	9.3
15L		1289	118	B1-U3-G1	1435	132	B1-U3-G1	1278	117	B1-U3-G1	1275	117	B1-U3-G1	1275	117	B1-U3-G1	10.9
17L		1458	114	B1-U3-G1	1623	127	B1-U3-G1	1445	113	B1-U3-G1	1443	113	B1-U3-G1	1443	113	B1-U3-G1	12.8

*Photometric performance values shown are representative with CGG6 clear glass globe option. Alternate glass globe option outputs will vary. Consult factory.

ELECTRICAL DATA*					
Lumen Package	Wattage	120V	208V	240V	277V
12L	9.3	0.08	0.04	0.04	0.03
15L	10.9	0.09	0.05	0.05	0.04
17L	12.8	0.11	0.06	0.05	0.05

*Electrical data at 25C (77F). Actual wattage may differ by +/-10%.



PRODUCT DIMENSIONS

Prefix	Height (A)	Diameter (B)
WAR 610	10-1/4" (260mm)	10" (254mm)
WAR 616	10-1/4" (260mm)	16" (406mm)
WAR 610W	10-1/4" (260mm)	10" (254mm)
WAR 616W	10-1/4" (260mm)	16" (406mm)

