



Catalog # : \_\_\_\_\_ Project : \_\_\_\_\_

Prepared By : \_\_\_\_\_ Date : \_\_\_\_\_

# CEC

## Compact Exit Combo



### FEATURES & SPECIFICATIONS

#### Construction

- Injection-molded UL 94 5VA flame retardant, corrosion resistant, thermoplastic housing
- All configurations include field-selectable directional chevrons
- Standard finish: White and Black

#### Optical

- Backlit red or green LEDs with color matched lens for bright even illumination
- Dual adjustable 1W LED lamps provide 150 lumens at 6000K
- Fully-illuminated 6" characters with 3/4" stroke

#### Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Test button to provide manual verification of the transfer circuit and emergency lamps
- RC option compatible with RRL and CRL remote heads

#### Battery

- Maintenance free NiCad Battery
- Operating Temperature 0°C to 40°C (0°F to 104°F)
- RC option requires Ni-MH Battery

#### Installation

- Includes two faceplates, back plate, and mounting bracket for wall, ceiling, and end mount

- Back plate provides J-box mounting pattern with keyhole slots

#### Warranty

- 3 year warranty on all electronics and housing
- Separate 3 year pro-rated warranty on the battery

#### Listings

- UL 924
- NFPA 701
- NEC
- UL Listed 90 minute emergency run time, 24 hour recharge time
- Suitable for Damp Location

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **CEC R WH SD2 RC**

Prefix	Letter Color	Housing Color	Options
<b>CEC</b> - Compact Exit Combo	<b>R</b> - Red <b>G</b> - Green	<b>WH</b> - White <b>BK</b> - Black	<b>SD2</b> - Self Test/Self Diagnostic <b>RC<sup>1</sup></b> - 4W Remote Capacity <b>WGB1</b> - Wire Guard Back Mount <b>PGB6</b> - Polycarbonate Guard Back Mount

1 - RC option supplied with Ni-MH battery

### PRODUCT DIMENSIONS

