



Catalog # : _____ Project : _____

Prepared By : _____ Date : _____

ELXC

Edge-lit Exit Combo



FEATURES & SPECIFICATIONS

Construction

- Surface Mount - Extruded aluminum housing with mounting bracket
- Recessed Mount - Steel housing supplied with galvanized steel adjustable hanger bar assembly
- All configurations include field-selectable directional chevrons
- Includes clear single-face and mirrored double-face panel configurations
- Standard finish: Satin Aluminum, White, Black

Optical

- Illuminated by long-life, high intensity red or green LEDs with 2.5W LED lamps (non-SD2 option) or 1.5W lamps (SD2 option)
- Fully-illuminated 6" characters with 3/4" stroke

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Low voltage disconnect eliminates deep discharge
- Compatible with two RRL remote lamps with non-SD2 option and one RRL with SD2 option
- Test button to provide manual verification of the transfer circuit and emergency lamps

Battery

- Maintenance free NiMH Battery
- Operating Temperature 5°C to 40°C (41°F to 104°F)

Installation

- Surface mounting includes wall or ceiling mounting bracket and all hardware

- Recessed mounting includes mounting bracket and all hardware for recessed ceiling and recessed wall mounting applications. Electronics and battery contained in housing. Plug-in battery connector supplied for easy installation.

Warranty

- 10 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery.

Listings

- UL 924
- NPFA 101
- NEC
- California Energy Commission (CEC) compliant
- UL Listed 90 minute emergency run time, 24 hour recharge time
- Suitable for Damp Location

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **ELXC S R WH SD2**

Prefix	Mounting	Letter Color	Housing Color	Options
ELXC ¹ - Edge-lit Exit Combo	S - Surface - Ceiling, End, or Wall Mount RE - Recessed	R - Red G - Green	WH - White BK - Black SA - Satin Aluminum	SD2 ² - Self Test/Self Diagnostic RC ³ - 3W Remote Capacity

1 - Includes single clear face and double mirror face panels
 2 - SD2 option uses 1.5W lamp heads
 3 - RC option compatible with two RRL with non-SD2 models or one RRL with SD2 models

PRODUCT DIMENSIONS

