



Catalog # : \_\_\_\_\_ Project : \_\_\_\_\_

Prepared By : \_\_\_\_\_ Date : \_\_\_\_\_

# LBC

## Light Bar Combo



damp location



### FEATURES & SPECIFICATIONS

#### Construction

- Injection-molded UL 94 5VA flame retardant, high temperature thermoplastic housing
- Adjustable integrated light bar
- All configurations include field-selectable directional chevrons
- Standard finish: White and Black

#### Optical

- Illuminated by long-life, high intensity red or green LEDs
- 1.5W bright-white LED light bar
- Fully-illuminated 6" characters with 3/4" stroke

#### Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Low voltage disconnect eliminates deep discharge with SD2 option
- Brownout circuit monitor with SD2 option
- Short circuit and voltage surge protection
- Test button to provide manual verification of the transfer circuit and emergency lamps
- Standard Remote Compatible of up to two SRL remote heads

#### Battery

- Maintenance free NiCad Battery
- Operating Temperature 0°C to 40°C (32°F to 104°F)

#### Installation

- Includes mounting bracket for ceiling and end mount
- Dual Face (2F) option snap together design allows for fully interchangeable universal faceplate and back plate

#### Warranty

- 5 year warranty on all electronics and housing.
- Separate 5 year pro-rated warranty on the battery.

#### Listings

- UL 924 Damp Location
- NFPA 101
- NEC
- UL Listed 90 minute emergency run time, 24 hour recharge time

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **LBC R 1F WH SD2**

Prefix	Letter Color	# of Faces	Housing Color	Options
LBC - Light Bar Combo	R - Red G - Green	1F - Single Face 2F - Dual Face	WH - White BK - Black	SD2 - Self Test/Self Diagnostic WGB1 - Wire Guard Back Mount WGE - Wire Guard End Mount WGC - Wire Guard Ceiling Mount PGB6 - Polycarbonate Guard Back Mount

### PRODUCT DIMENSIONS

