



Catalog #: \_\_\_\_\_ Project: \_\_\_\_\_

Prepared By: \_\_\_\_\_ Date: \_\_\_\_\_ Type: \_\_\_\_\_

# VE

## Value Edge-Lit Exit Sign



### FEATURES & SPECIFICATIONS

#### Construction

- Extruded aluminum housing with high-grade acrylic panel
- Pivoting design for simple installation
- Compact low-profile design for ease of maintenance
- Mirror panel standard on double-face signs
- All configurations include field-selectable directional chevrons
- Standard finish: White and Satin Aluminum

#### Optical System

- Illuminated by long-life, high intensity red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke

#### Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Low voltage disconnect eliminates deep discharge
- Test button to provide manual verification of the transfer circuit and emergency lamps

#### Battery

- Maintenance free NiCad Battery (WB only)
- Operating Temperatures 0°C to 40°C (32°F to 104°F)

#### Installation

- All configurations include universal surface and recessed mounting kits
- Universal surface ceiling, end, or wall mounting

- Recessed ceiling mount accessible above the plenum with electronics and battery contained in housing

#### Warranty

- 3 year warranty on all electronics and housing
- Separate 2 year pro-rated warranty on the battery

#### Listings

- UL 924
- NFPA 101
- NEC
- CEC
- Damp Location Rated
- UL Listed 90 minute emergency run time, 24 hour recharge time

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **VE U 6 R 1C WB WH SD2**

Prefix	Mounting	Character Size	Letter Color	# of Faces	Battery	Housing Color	Options
VE - Value Edge-Lit Exit Sign	U - Universal Surface Ceiling, End, or Wall Mount and Recessed Mount	6 - 6" Tall Letters 3/4" Stroke	R - Red G - Green	1C - Single Face Clear 2M - Double Face Mirror	LB - Less Battery WB - With Battery	WH - White SA - Satin Aluminum	SD <sup>1</sup> - Self Test / Self Diagnostic

FOOTNOTES:  
1 - Not available with LB option

### PRODUCT DIMENSIONS

