



Catalog # : \_\_\_\_\_ Project : \_\_\_\_\_

Prepared By : \_\_\_\_\_ Date : \_\_\_\_\_

# WLEC

## Wet Location Exit Combo



wet location



### FEATURES & SPECIFICATIONS

#### Construction

- UV stabilized, impact and corrosion resistant 5VA plastic housing with one-piece, molded, weather-proof gasket
- Impact-resistant, polycarbonate shielded enclosure
- All configurations include field-selectable directional chevrons
- Standard finish: White, Black, and Gray

#### Optical

- Illuminated by long-life, high intensity red or green LEDs
- Dual adjustable 3.6W LED lamps
- Fully-illuminated 6" characters with 3/4" stroke

#### Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Low voltage disconnect eliminates deep discharge with SD2 option
- Brownout circuit monitor with SD2 option
- The WLEC provides manual testing by

utilizing a magnet against the unit in a specific pattern:

- To initiate a 30 second test, touch and pull away magnet once within two seconds; FLASHING Green
- To initiate a 30 minute test, touch and pull away magnet twice within two seconds; BLINKING Green 2 times
- To initiate a 90 minute test, touch and pull away magnet three times within two seconds; BLINKING Green 3 times
- Interruption, touch and hold magnet for 3-5 seconds
- System reset, touch and hold magnet for more than six seconds
- RC option provides an additional 7.2W of remote power compatible with RRL lamps

#### Battery

- Maintenance free NiCad Battery
- Operating Temperature 0°C to 50°C (32°F to 122°F)
- CW cold weather option extends operating range to -20°C to 50°C (-4°F to 122°F)

#### Installation

- Universal Mounting: ceiling, wall, end mount
- Universal knockout on back plate allows for wall mount
- Die-cast aluminum mounting plate allows for ceiling and end mount

#### Warranty

- 5 year warranty on all electronics and housing.
- Separate 5 year pro-rated warranty on the battery.

#### Listings

- UL 924 Wet Location
- NFPA 101
- NEC
- California Energy Commission (CEC) compliant
- UL Listed 90 minute emergency run time, 24 hour recharge time

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **WLEC R 1F WH SD2 CW**

Prefix	Letter Color	Output	Housing Color	Options
WLEC - Wet Location Exit Combo	R - Red G - Green	1F - Single Face 2F - Dual Face	WH - White BK - Black GR - Gray	SD2 - Self Test/Self Diagnostic CW - Cold Weather RC - 7.2W Remote Capacity WGB5 - Wire Guard Back Mount PGB6 - Poly Guard Back Mount

### PRODUCT DIMENSIONS

